



This certifies that

ECZACIBASI BUILDING MATERIALS VITRA FAUCET DIVISION

has had the undermentioned product examined, tested and found, when correctly installed, to comply with the requirements of the United Kingdom Water Supply (Water Fittings) Regulations and Scottish Water Byelaws.

A42361VUK COMBINATION TAP ASSEMBLY

The certificate by itself is not evidence of a valid WRAS Approval. Confirmation of the current status of an approval must be obtained from the WRAS Directory (www.wras.co.uk/directory)

The product so mentioned will be valid until the end of:

June 2020

1506319

Certificate No.

A handwritten signature in black ink, appearing to read 'H. Turner'.

Secretary

A handwritten signature in black ink, appearing to read 'K. ...'.

Chairman, Product Assessment Group



Approval No: 1506319

Water Regulations Advisory Scheme Ltd.
Unit 13,
Willow Road,
Pen y Fan Industrial Estate,
Crumlin,
Gwent,
NP11 4EG

10th June 2015

Eczacıbasi Building Materials VITRA Faucet Division,
4 Eylül Mah.
İnönü Cad.
Duzdag Yolu 1 No: 4,
11300,
Bozuyuk Bilecik,
Turkey

Dear Sir/Madam

COMBINATION TAP ASSEMBLIES

1. Samples of the fittings or units described below have been subjected to relevant tests and examinations contained in the "Regulators' specifications", and after considering the test reports the Technical Committee's Product Assessment Group (PAG) of the Water Regulations Advisory Scheme (WRAS or "the Scheme") finds that the fittings or units so described comply with, and their use when correctly installed, does not contravene the requirements of The Water Supply (Water Fittings) Regulations 1999, The Water Byelaws 2004 Scotland, and Water Supply (Water Fittings) Regulations (Northern Ireland) 2009.

1506319

This approval is valid for fittings (as listed below in model) manufactured AND installed between June 2015 & June 2020

COMBINATION TAP ASSEMBLIES

0450

Single Hole - Metal Single Outlet - Fixed

IRN R001, R010, R150

Single hole, single outlet (fixed) combination tap assembly (chromium plated brass). Incorporating ceramic cartridge headwork, single lever operating member. The spout outlet incorporates a plastic aerator. Maximum working pressure 10.0 bar. Maximum operating temperature 90 C.

Size: Stainless steel braided EPDM lined flexible hose assemblies with 1/2" captive nut end connections

Model: A42361VUK


Marking: Vitra on operating member

Manufacturer: Eczacıbaşı Building Materials VITRA Faucet Division

2. Installation Requirements & Notes are set out on Page 3.
3. Fittings or units (and any non-metallic components contained within them) are re-assessed and, where necessary, retested every 5 years. You will be advised when your product is due for re-assessment. The extent of any retesting required for a product will be at the discretion of the Technical Manager.
4. **Acceptance for listing entitles you to identify your product with the Scheme's "WRAS" Mark. The use of the Mark will make the identification easier of the approved products by Water Undertakers.** Copies of the 'Mark' are available on request for the purposes of producing artwork.
5. Manufacturers or applicants may only quote in their sales literature, terms used in this letter when indicating the decision of the Group in respect to their fittings or units, namely that the **Product Assessment Group of the Scheme finds that the use of these fittings or units, when correctly installed, will not contravene the requirements of The Water Supply (Water Fittings) Regulations 1999, The Water Byelaws 2004 Scotland or The Water Regulations (Northern Ireland) 2009 and that a reference to the fittings or units will be included in the Scheme's Water Fittings and Materials Directory:** this may be abbreviated to "Water Regulations Advisory Scheme - Approved Product" or "WRAS - Approved Product".
6. Since the incorrect installation of water fittings could result in contravention of the Regulations or Byelaws requirements, **the attention of your customers should be drawn to any Installation Requirements for Regulations or Byelaws compliances set out on Page 3.**
7. Would you please supply the Scheme with a copy of any of your company's literature which may or will make reference to the Scheme's decisions about the products and/or quotes any of the installation requirements.
8. A condition of listing is that **no modification to the fittings or units described above shall be made without first notifying the Scheme** and submitting to the Scheme details of the modification and, if so required, samples of the fittings or units as so modified for consideration by the Scheme's Product Assessment Group. Failure to comply with this condition may result in the removal from the Water Fittings and Materials Directory of the entry relating to the fittings or units in question.
9. Your products are required to be replicas of the samples described above, and the right is reserved to carry out quality surveillance inspections of your production arrangements, reasonable written notice of which will be given.
10. Please note that the use of the items described in any particular area of supply is at the discretion of the local Water Undertaking.

11. Manufacturers or factors having appliances or units referred to in the Scheme's Directory which incorporate individually approved components and materials are asked to ensure that such components and materials continue to be approved and/or listed in the Directory, during the current period of approval of their appliance. This may require modifications to approved appliances to ensure their retention in the Scheme's Directory. The Scheme must be informed of any such modifications, (see paragraph 8).
12. You are asked to verify the details of your product as set out in Paragraph 1 and advise us of any discrepancies.

Yours sincerely



Jason Furnival
Secretary, Product Assessment Group

INSTALLATION REQUIREMENTS & NOTES

You are advised to draw customers' attention to the installation requirements and notes set out below which must be followed to ensure that the fittings described above are installed in accordance with the requirements of the Regulations and Byelaws:

IRN R001

See text of entry for Installation Requirements or Notes.

IRN R010 Schedule 2-15 (1)

Water supplies shall be at reasonably balanced pressures from a common source (e.g. hot and cold supplies both from the same storage or both from a supply pipe). Where the fitting is supplied from unbalanced supplies (e.g. hot and cold supplies from separate sources) a '**Listed**' **single check valve** or some other no less effective backflow prevention device shall be fitted immediately upstream of both hot and cold water inlets.

IRN R150

An 'Approved' single check valve or some other no less effective backflow prevention device providing backflow prevention protection to at least fluid category two shall be fitted at the point of connection(s) between the water supply and the fitting or appliance.

PAG. 1506319



Water Regulations Advisory Scheme Ltd.
Unit 13,
Willow Road,
Pen y Fan Industrial Estate,
Crumlin,
Gwent,
NP11 4EG

Eczacibasi Building Materials VITRA Faucet Division,
4 Eylul Mah.
I.inonu Cad.
Duzdag Yolu 1 No: 4,
11300,
Bozuyuk Bilecik,
Turkey

Dear Sir/Madam

RE: USE OF WATER REGULATIONS ADVISORY SCHEME WRAS APPROVED LOGO

All manufacturers and factors with products approved by WRAS may use the scheme's approved logo.

Whilst this is not mandatory we would encourage that wherever practicable all WRAS approved products, including their associated packaging and literature, are suitably marked with the WRAS logo.

The WRAS logo artwork is available on request.

Should you require any further information regarding this matter please do not hesitate to contact me.

Yours sincerely

A handwritten signature in black ink, appearing to read 'Jason Furnival', written over a horizontal line.

Jason Furnival
Secretary, Product Assessment Group